



AN EASY-TO-USE USB VIDEO BAR FOR SMALL CONFERENCE SPACES

BENEFITS

- Poly DirectorAI technology ensures everyone is seen clearly with pinpoint-accurate automatic framing and tracking.
- Connect to Poly Lens over Wi-Fi to ensure the device can always be managed from anywhere, even when not connected to a computer.**
- Hear pristine clarity and rich sound with a powerful integrated speaker featuring acoustic suspension with a passive radiator.
- Make sure you're always heard clearly with an advanced multi-microphone array.
- Prevent distracting noises and side conversations from interrupting your meetings with NoiseBlockAI and Acoustic Fence technologies.

POLY STUDIO R30

The Poly Studio R30 USB video bar offers a dynamic camera experience that ensures everyone is seen clearly — making meetings easier and more inclusive than ever, with Poly DirectorAI technology. Enjoy rich audio that filters out background noise and makes sure everyone is heard clearly. IT managers love how easy it is to set up, manage, and deploy and with cloud-based Poly Lens management functionality, it's a win-win. This plug-and-play video bar offers maximum meeting quality with minimum hassle.

- Sharp 4K camera with 120-degree field of view.
- Poly DirectorAI smart camera technology.
- Powerful integrated speaker.
- Multi-microphone array.
- Works with any video app on your PC or Mac.

POLY STUDIO R30



SPECIFICATIONS

CAMERA

- Ultra HD (4K 16:9, 2160p), Full HD (1080p), HD (720p)
- 30 fps
- 120° DFOV, 110° HFOV
- True color and low light compensation
- Automatic meeting experience powered by Poly DirectorAI technology including group framing, people framing (preview), speaker framing, presenter tracking and conversation mode (preview)
- Electronic zoom up to 5x*
- Manual pan, tilt and zoom control through Poly Lens Desktop App

AUDIO

- Poly Acoustic Clarity technology with advanced acoustic echo cancellation and background noise suppression
- Poly NoiseBlockAI technology
- Poly Acoustic Fence technology
- Microphones: 3-element beamforming microphone array
 - 50 Hz to 14 kHz frequency response

SPEAKER

- 100 Hz to 20 kHz frequency response
- Output: 84 dB SPL @ 1000 Hz @ 1 meter at maximum volume

INTERFACES

- 1x USB 3.0 Type-C port (with USB 2.0 compatibility)
- 2x USB 2.0 Type-A ports
- Power connector
- Kensington security lock
- 802.11ac Wi-Fi wireless networking for manageability; IEEE 802.11a/b/g/n compatible**
- Bluetooth® 4.2**

POWER REQUIREMENTS

- External DC power supply: 12V/3A

SYSTEM REQUIREMENTS

- Windows 8.1, 10, 11
- Mac OS 10.10 or higher
- USB 3.0 required for 4K video

DEVICE DRIVER SUPPORT

- USB 2.0/3.0/3.1
- UVC/UAC Plug and Play Compatible

COMPATIBILITY

- Compatible with any application that supports standard USB audio and video drivers
- Certified for Zoom Rooms
- Microsoft Teams compatible

MANAGEABILITY

- Cloud: Poly Lens service
- Local (Windows/Mac): Poly Lens Desktop App

SECURITY

- 802.1x support**
- Certificate management

OTHER FEATURES

- Adjustable monitor clamp
- Standard Tripod thread
- Inverted mounting option
- USB-A ports built-in for wireless headset adapter or other peripherals as USB hub
- Status LED indicates calling and mute state

DIMENSIONS AND WEIGHTS

With monitor clamp:

- 17.5 W x 3.4 H x 3.2 D (inches)
- 445 W x 86 H x 81 D (mm)
- 1 lb 13 oz/822 g

LEARN MORE

For more information on Poly Studio R30 visit poly.com/studio-r30

Without monitor clamp:

- 17.5 W x 2.7 H x 3.2 D (Inches)
- 445 W x 68 H x 81 D (mm)
- 1 lb 10 oz/737 g

OPERATING CONDITIONS

- Temperature: 0° C to +40° C
- Relative humidity: 15% to 80% relative humidity, non-condensing
- Altitude: Up to 16,000 ft

PACKAGE CONTENTS

- Poly Studio R30 USB video bar
- Removable monitor clamp
- Power supply (1.5 m/4.9 ft)
- Power cord (2.7 m/9 ft)
- USB 2.0 cable (Type-C to Type-A, 5 m/16.4 ft)
- Setup sheet
- Removable privacy cap

OPTIONAL ACCESSORIES

- Bluetooth remote control**
- Wall mount

WARRANTY


- 1-year limited warranty included
- Poly+ enhanced support available

*Up to 5x zoom without tracking, and 4x zoom with auto tracking.

**Not available on no radio versions.

ClickShare CX-20

Conferenze wireless semplici per sale riunioni di piccole dimensioni e spazi ristretti



- **Modello per conferenze wireless entry-level**
- **Esegui riunioni video dal tuo laptop**
- **L'iconico dispositivo ClickShare Button per dipendenti e ospiti**
- **100% sicuro, crittografato e gestito dal cloud**

ClickShare CX-20 consente conferenze wireless in piccoli spazi per riunioni. Quando entri nella sala riunioni, ClickShare ti connette automaticamente ai dispositivi della sala come fotocamere, microfoni, altoparlanti, soundbar e display.

Avvia una riunione dal tuo laptop in pochi secondi, utilizzando la tua piattaforma di videoconferenza preferita. Semplifica le riunioni ibride, con un solo clic sul pulsante ClickShare o sull'app ClickShare, sia per i dipendenti che per gli ospiti.

Specifiche tecniche

CLICKSHARE CX-20

Dimensioni dell'unità di base ClickShare

Dimensioni (AxLxP)	34 mm x 135 mm x 135 mm
Alimentazione	Spina CA da 110/220 V standard o USB-C
Consumo energetico	Funzionamento: 5 -10 W, 24 W max
Peso	900 gr

Specifiche generali

Sistema operativo	Windows 10 e versioni successive macOS 11 (BigSur) e versioni successive. Android v11 e versioni successive (app ClickShare) iOS 14 e versioni successive (app ClickShare)
Requisiti di sistema	Per un'esperienza fluida con Microsoft Teams o Zoom. Minimo: Processore Intel i3 dual-core /8 GB di RAM / OS: Windows 10 ultima build o ultima build Mojave Consigliato: Intel i5 processore a 4 core / 8 GB di RAM / OS: Windows 10 ultima build o Mac OS ultima build
Uscite video	4K UHD (3840 x 2160) a 30 Hz. HDMI 1.4b o USB-C DisplayPort 1.2
Uscita audio	USB, HDMI
USB	1 USB-A, 1 USB-C
ClickShare Button	1
ClickShare App	Desktop e dispositivi mobili
Native protocols	AirPlay, Google Cast, Miracast

Numero massimo di connessioni simultanee (con Button e/o App)

Livello di rumore	Max 25 dBA a 0 -30 °C Max 30 dBA a 30 -40 °C
Protocollo di autenticazione	WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode
Protocollo di trasmissione wireless	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
Portata	Max: 30 m (100 piedi) tra ClickShare Button e ClickShare Base Unit Banda di frequenza 2,4 GHz e 5 GHz (DFS)
Banda di frequenza	2,4 GHz e 5 GHz (canali DFS supportati in alcuni paesi)
Connessioni	1 LAN Ethernet 1 Gbit 1 USB Type-C 2.0 (anteriore); 1 USB Type-A 2.0 (anteriore)
Intervallo di temperature	Funzionamento: da 0 °C a +40 °C (da +32 °F a +104 °F) Max: 35 °C (95 °F) a 3000 m Stoccaggio: da -20 °C a +60 °C (da -4 °F a +140 °F)
Umidità	Stoccaggio: da 0 a 90% di umidità relativa, senza condensa Funzionamento: da 0 a 85% di umidità relativa, senza condensa
Sistema antifurto	Lucchetto Kensington
Certificazioni	FCC/CE
Touch screen support & Interactivity	/
Conferenze wireless	tramite app o Button
Vista locale	Vista locale solo del display della stanza
Connessione in rete	LAN e Wi-Fi*
Management and reporting	Si
Garanzia	1 anno standard, 5 anni di copertura tramite SmartCare

Generato il: 30 May 2024

© 2024 Barco nv. Tutti i diritti riservati. La riproduzione totale o parziale è proibita in assenza di autorizzazione scritta. Tutti i nomi di marchi e di prodotti sono marchi, marchi registrati o nomi commerciali dei rispettivi proprietari. A causa delle continue innovazioni, le informazioni e le specifiche tecniche sono soggette a modifiche senza preavviso. Controlla www.barco.com per le specifiche più recenti.