

ClickShare CX-30

Conferenze wireless senza interruzioni per sale riunioni e conferenze di piccole e medie dimensioni



- **Funzionalità interattive:** touchback, annotazione e lavagna
- **Maggiore collaborazione** con 2 sorgenti a schermata
- **Gestisci riunioni video dal tuo laptop con Button o App**
- **100% sicuro,** crittografato e gestito dal cloud

ClickShare CX-30 consente conferenze wireless in sale riunioni di medie dimensioni. Quando entri nella sala riunioni, ClickShare ti connette automaticamente ai dispositivi della sala come fotocamere, microfoni, altoparlanti, soundbar e display.

Avvia una riunione dal tuo laptop in pochi secondi, utilizzando la tua piattaforma di videoconferenza preferita. Semplifica le riunioni ibride, con un solo clic sul pulsante ClickShare o sull'app ClickShare, sia per i dipendenti che per gli ospiti.

Specifiche tecniche

CLICKSHARE CX-30

Dimensioni dell'unità di base ClickShare

Dimensioni (AxLxP)	34 mm x 135 mm x 135 mm
Alimentazione	Spina CA da 110/220 V standard o USB-C
Consumo energetico	Funzionamento: 5 -10 W, 24 W max
Peso	900 gr

Specifiche generali

Sistema operativo	Windows 10 e versioni successive macOS 11 (BigSur) e versioni successive. Android v11 e versioni successive (app ClickShare) iOS 14 e versioni successive (app ClickShare)
Requisiti di sistema	Per un'esperienza fluida con Microsoft Teams o Zoom. Minimo: Processore Intel i3 dual-core /8 GB di RAM / OS: Windows 10 ultima build o ultima build Mojave Consigliato: Intel i5 processore a 4 core / 8 GB di RAM / OS: Windows 10 ultima build o Mac OS ultima build
Uscite video	4K UHD (3840 x 2160) a 30 Hz. HDMI 1.4b o USB-C DisplayPort 1.2
Uscita audio	USB, HDMI
USB	1 USB-A, 1 USB-C
ClickShare Button	2
ClickShare App	Desktop e dispositivi mobili
Native protocols	AirPlay, Google Cast, Miracast

Numero massimo di connessioni simultanee (con Button e/o App)

Livello di rumore	Max 25 dBA a 0 -30 °C Max 30 dBA a 30 -40 °C
Protocollo di autenticazione	WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode
Protocollo di trasmissione wireless	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
Portata	Max: 30 m (100 piedi) tra ClickShare Button e ClickShare Base Unit Banda di frequenza 2,4 GHz e 5 GHz (DFS)
Banda di frequenza	2,4 GHz e 5 GHz (canali DFS supportati in alcuni paesi)
Connessioni	1 LAN Ethernet 1 Gbit 1 USB Type-C 2.0 (anteriore); 1 USB Type-A 2.0 (anteriore)
Intervallo di temperature	Funzionamento: da 0 °C a +40 °C (da +32 °F a +104 °F) Max: 35 °C (95 °F) a 3000 m Stoccaggio: da -20 °C a +60 °C (da -4 °F a +140 °F)
Umidità	Stoccaggio: da 0 a 90% di umidità relativa, senza condensa Funzionamento: da 0 a 85% di umidità relativa, senza condensa
Sistema antifurto	Lucchetto Kensington
Certificazioni	FCC/CE
Touch screen support & Interactivity	Sì
Conferenze wireless	tramite app o Button
Vista locale	Sì
Connessione in rete	LAN e Wi-Fi*
Management and reporting	Sì
Garanzia	1 anno standard, 5 anni di copertura tramite SmartCare

Generato il: 30 May 2024

© 2024 Barco nv. Tutti i diritti riservati. La riproduzione totale o parziale è proibita in assenza di autorizzazione scritta. Tutti i nomi di marchi e di prodotti sono marchi, marchi registrati o nomi commerciali dei rispettivi proprietari. A causa delle continue innovazioni, le informazioni e le specifiche tecniche sono soggette a modifiche senza preavviso. Controlla www.barco.com per le specifiche più recenti.

Poly Studio E70 Smart Camera

As good as being together

The Poly Studio E70 is an intelligent camera that brings clear video quality, and advanced analytics to meeting rooms. Dual cameras are boosted by Poly DirectorAI technology to create a vibrant video experience.



*Product image may differ from actual product

Crystal clear video

Experience lifelike clarity in your large meeting rooms with an intelligently built camera made for hybrid working environments. And with the dual camera and seamless transitions – everyone is seen in sharp detail.

Intelligent camera technology

An artistically engineered meeting experience and AI come together to create Poly DirectorAI smart camera technology. Choose between different framing and tracking modes to create the most equitable experience for your hybrid meetings.

Poly Studio E70 Smart Camera

Featuring



Dual camera with 4K sensors

Dual camera with 20-megapixel 4K sensors creates a vibrant video experience. Seamlessly transition between a wide angle and narrow lens so everyone can be seen in sharp detail.

AI-driven camera array

Poly DirectorAI smart camera technology ensures everyone is seen clearly with pinpoint accurate automatic framing.

Privacy shutter

Keep your meeting room conversations private when they need to be with a motorized, integrated electronic privacy shutter for peace of mind.

Easy management via Poly Lens

Take control of your deployment from anywhere via remote management with Poly Lens cloud-based device management software.

Communications platforms

Connects easily to Microsoft Teams Rooms on Windows, Zoom Rooms on Windows, Poly Studio G62 and Poly G7500 for streamlined deployments.¹

Datasheet

Poly Studio E70 Smart Camera

Specifications

Camera

Camera resolution: 2160p, 4K UHD (3840 x 2160)
Diagonal field of view (dFoV): 78°; 140°
Horizontal field of view (hFoV): 120°; 70°
Total Camera Megapixels: 2 x 20 MP
Zoom capability: 7.3x digital
Camera type: Dual-Lens
Lens privacy capabilities: Integrated
Camera range (metric): Up to 7.62 m
Camera range (imperial): Up to 25 ft
Smart camera technology: Poly DirectorAI with speaker framing; People framing; Group framing; DirectorAI perimeter

Connectivity and communications

External I/O ports:
1 USB Type-C® 5Gbps signaling rate
1 RJ-45

Audio

Power adapter port: 1 x 4.5 mm

Other features

Special features: Meeting participant counting; Electronic privacy shutter

Power supply

Power supply type: External
Power features: 100 - 240 VAC 50/60 Hz, 1.5A input
12 VDC, 5A, 60 W output
Power over Ethernet (PoE), 802.3af, 15.4 W, Class 3

Environmental

Operating Altitude (imperial) / Operating Altitude (metric): 16,000 ft / 4,877 m
Operating humidity range: 15 to 80%
Non-operating humidity range: 5 to 95%
Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): 0 to 40 °C / 32 to 104 °F
Non-operating temperature - Celsius: -40 to 70 °C
Non-operating temperature - fahrenheit: 40 to 158 °F

Management

Management software:
Poly Lens

Weight and dimensions

Product Primary Color: White
Weight (imperial): 2 lb
Weight (metric): 907 g
Product dimensions (imperial): 12.63 x 4.02 x 3.51 in
Product Dimensions (metric): 321 x 102 x 89.1 mm
Master carton dimension (imperial): 9.64 x 17.32 x 11.61 in
Master carton dimension (metric): 24.5 x 44 x 29.5 cm
Cartons per layer: 21
Pallet (layers): 9
Cartons per pallet: 189
Products per layer: 21
Products per pallet: 189
Pallet weight: 787.05 lb; 357 kg
Pallet dimensions (imperial): 40 x 48 x 58.66 in
Pallet dimensions (metric): 101.6 x 121.9 x 149 cm
Product number: 842F8AA
Product name: Poly Studio E70 Smart Camera

Warranty

Poly standard one-year limited warranty

Country of origin

Country of origin: Made in Laos

What is in the box

Poly Studio E70
Ethernet cable
Wall mount kit
USB Type-A to USB Type-C® cable

Feature Messaging Footnotes

¹ Visit <https://www.poly.com/us/en/products/video-conferencing/studio/studio-e70> for more detail.

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.
October 2024

Datasheet