

Ports	3× 10/100 Mbps LAN ports 1× 10/100 Mbps LAN/WAN Port 1× Micro SIM Card Slot
Tasto	WPS/Reset Button, Wireless On/Off Button, Power On/Off Button
External Power Supply(EU)	9V/0.85A
Dimensioni (L x P x A)	6.85 × 4.9 × 1.32 in. (174 × 124.5 × 33.5 mm)
Tipo di antenna	2× Detachable External 4G LTE Antennas

CARATTERISTICHE WIRELESS

Standard wireless	IEEE 802.11b, 802.11g, 802.11n
Frequenza	2.4GHz
Signal rate	300Mbps at 2.4GHz
Sensibilità di ricezione	11g 54M: -74 dBm 11n HT20: -71 dBm 11n HT40: -67 dBm
Potenza di trasmissione	<20 dBm (2.4 GHz)
Funzionalità wireless	Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics
WAN Failover	Yes
Sicurezza wireless	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
Tipo di rete	4G: FDD-LTE Cat4 (800/900/1800/2100/2600 MHz), TDD-LTE (2300/2500/2600 MHz) 3G: DC-HSPA+/HSPA+/HSPA/UMTS (900/2100 MHz)

CARATTERISTICHE SOFTWARE

QoS (Quality of Service)	WMM, QoS
Modalità operative	3G/4G Router, Wireless Router
Gestione	Access Control, Local Management, Remote Management
Tipo connessione WAN	Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
DHCP	Server, Client, DHCP Client List, Address Reservation
Port forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	TP-Link DDNS, DynDns, NO-IP
VPN pass-through	PPTP, L2TP, IPSec
Gestione accessi	Parental Controls, Local Management Control, Host List, Access Control
Firewall	DoS, SPI Firewall, IP and MAC Address Binding
Protocolli	Supports IPv4 and IPv6
Rete ospiti	2.4 GHz Guest Network
VPN Server	PPTP VPN, OpenVPN

ALTRO

Certificazione	CE, RoHS
Contenuto della confezione	300Mbps Wireless N 4G LTE Router TL-MR6400 Power Adapter RJ45 Ethernet Cable Quick Installation Guide
Requisiti di sistema	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browser or higher, or other Java-enabled browsers Micro SIM Card
Ambiente	Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~60°C (-40°F ~140°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing