

Exceptional durability, stunning visuals in outdoor

Samsung OHDX series is built for tough environments, allowing you to captivate your audience daily by effectively delivering your business message beyond the storefront. Even in varying weather, the OHDX ensures your brand presence stays powerful and memorable with a dynamic customer experience.

Key features



Verified by UL Solutions for Outdoor Visibility

With a brightness level 3,500nits(peak 4000nit) delivering 24/7 performance, the OHDX series is designed to provide clear and vivid content in outdoor environment. OHDX is verified by UL for outdoor visibility brightness, ensuring your message is effectively communicated even in direct sunlight.



Heat dissipation structure

Featuring an advanced heat dissipation system for efficient air circulation, the OHDX series' design prevents heat damage, common in outdoor displays with high-brightness. The display's effective cooling measures help ensure stable and reliable performance in tough environments.



IP56

With certified IP56-rated protection, OHDX series delivers a dustproof and waterproof design that also withstands physical impacts to protect the display. The ensures dependable operation in a variety of outdoor conditions for consistent performance.

* IP56 (Ingress Protection Rating): Degrees of protection provided by enclosures. (IEC 60529)



2nd Glass Installable Structure

Extend the exceptional durability of OHDX further with an optional compatible protective glass addition. Featuring an enhanced heat dissipation structure, the OHDX guarantees reliable performance when using the protective glass add-on, if desired.

 * Additional glass layer not included, must be purchased separately through a third party



Samsung VXT

Samsung VXT combines content and remote device management, allowing you to effortlessly manage hardware settings and troubleshoot issues while creating and deploying content.

* Samsung VXT must be purchased separatel

Specifications

	Model		OH55DX	OH46X
		Cl		
Display Panel	Diagonal Size	Class	55	46
		Measured	54.6" / 138.7cm	45.9"/116.8cm
	Resolution		1,920 x 1,080 (16:9)	1,920 x 1,080 (16:9)
	Brightness (Typ.)		3,500 nit (Peak 4,000 nit)	3,500 nit (Peak 4,000nit)
	Orientation		Landscape / Portrait	Landscape / Portrait
	Haze		0%	0%
	Contrast Ratio (Typ.)		6,000:1	6,000:1
	Type		VA	VA
	Active Display Area (mm)		1209.60(H) x 680.40(V)	1018.08(H) x 572.67(V)
	Pixel Pitch (mm)		0.630 x 0.630	0.53 x0.53
	ColorGamut		72 %	72 %
	Operation Hour		24/7	24/7
	VIDEO		HDMI 2.0 (2), HDBaseT (LAN Common)	HDMI 2.0 (2), HDBaseT (LAN Common)
		HDCP	HDCP 2.2	HDCP 2.2
Connectivity / Sound	INPUT	AUDIO	N/A	N/A
		USB	USB (2)	USB (2)
		Tuner	N/A	N/A
	OUTPUT	VIDEO	N/A	N/A
		AUDIO	Stereo mini Jack	Stereo mini Jack
		USB	N/A	N/A
	WiFi / BT		Yes (External Module Optional)	Yes (External Module Optional)
	EXTERNAL CONTROL		RS232C (In/Out), RJ45(In/Out), HDBaseT	RS232C (In/Out), RJ45(In/Out), HDBaseT
	Speaker		N/A	N/A
Mechanical Spec	Dimension (mm) Weight (kg)	Set	1,260.6 x 731.4 x 69.0	1,069 x 623.6 x 69.0
		Package	1,398 x 844 x 191	1,190 x 735 x 186
		J		28.2
		Set	36.7	
		Package	43.1	33.7
	VESA Mount VESA Mount Screw Hole Depth		1,186 x 560	995 x 500
	VESA Mount Screw, Hole Depth (Min ~ Max)		M8, 9~11	M8,9~11
	Bezel Wid	dth (mm)	24.9mm	24.9mm
Design	Bezel	Color	Black	Black
	Key		Power-box Integrated, IP56 Outdoor, Built-in	Power-box Integrated, IP56 Outdoor, Built-in
		Operating	MagicInfo Player S10, TEP, SmartThings, VXT Player	MagicInfo Player S10, TEP, SmartThings, VXT Player
Features	Internal Player	System	Tizen 8.0	Tizen 8.0
		Processor	Cortex A72 1.7GHz Quad-Core CPU	Cortex A72 1.7GHz Quad-Core CPU
		Storage (FDM)	8GB (3.88GB Occupied by O/S, 4.12GB Available)	8GB (3.88GB Occupied by O/S, 4.12GB Available)
		H/W	IP56, IK-10, Polarized Sunglasses Viewable, Brightness Sensor, Temperature Sensor, Kensington Lock	IP56, IK-10, Polarized Sunglasses Viewable, Brightness Sensor, Temperature Sensor, Kensington Loc
	Special		Auto Source Switching & Recovery	Auto Source Switching & Recovery
		S/W	RJ45 MDC	RJ45 MDC MS365, VXPlayer
	Safety		MS365, VXPlayer 60950-1, 62368-1	60950-1, 62368-1
Certification	EMC			
			Class A	Class A
	Environment		N/A	N/A
	IP Rating		IP56	IP56
	Security		N/A	N/A
Power	Power	Supply	AC100 - 240 V,50/60 Hz	AC100 - 240 V,50/60 Hz
	Power Consumption	Max [W/h]	580	480
		Typical [W/h]	N/A	N/A
	Sleep mode [W/h]		0.5	0.5
Operating	Tempe	erature	-30°C~ 50°C	-30°C~ 50°C
Condition	Relative Humidity		10~80% (Non-condensing)	10~80% (Non-condensing)
	Included		Quick Setup Guide Warranty Card Power Cord Remote Controller + Batteries	Quick Setup Guide Warranty Card Power Cord Remote Controller+ Batteries
Accessories		Stand	N/A	N/A
Accessories	Optional	Stand Mount	N/A N/A	N/A N/A

About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds

of TVs, smartphones, wearable devices, tablets, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

Smart Signage

For more information about Samsung Smart Signage, visit www.samsung.com/business

Copyright © 2024 Samsung Electronics Co., Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co., Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677 Republic of Korea